

Product Function	Exposed Shower Set, Handshower
Style Association	Heritage
Material	DR Brass
Handle Type	Cross Handle
Spindle Type	Splined Spindle
Cartridge / Valve	Jumper Valve
Turning Type	Full Turn Standard Action, is upgradable to Rapid Action (1/4 Turn) with Hydroseal Valve
Outlet Type	Fixed Position Rose
Outlet Styling	Straight Shower Arm
Outlet Reach (mm to Aerator or Rose)	450mm (500mm From Wall to Centre of Rose)
Outlet Type (Second Outlet)	N/A
Outlet Styling (Second Outlet)	Handshower
Outlet Reach (mm to Aerator or Rose) (Second Outlet)	1.5 Metre Hose
Outlet Type (Third Outlet)	N/A
Outlet Styling (Third Outlet)	No
Outlet Reach (mm to Aerator or Rose) (Third Outlet)	No
Water Efficiency Star (WELS) Rating	3 Stars (Handshower & Rose)
Flow Rate (Litres Per Minute)	9 Litres Per Minute
Suitable for Gravity Feed	Yes
Suitable for Hot Water Units	Yes
Maximum operating pressure (KPA)	Suitable for High/Mains Pressure / 500 KPA (Australian Standards AS/NZS 3500 and the Plumbing Code of Australia)
Maximum Working Temperature (Degree C)	65
Relevant Standards	AS/NZS 3718:2005
Quantity Unit of Measure	Set
Warranty	5 Years
WELS Licence	WELS Licence 0091
WELS Registration	S11676 (V)