

|   |  |
|---|--|
| <b>Product Function</b>                       | Bath Set, Vanity Sink Set  |
| <b>Style Association</b>                      | Roulette Lever   |
| <b>Material</b>                               | DR Brass   |
| <b>Handle Type</b>                            | Lever Handle   |
| <b>Spindle Type</b>                           | Splined Spindle  |
| <b>Cartridge / Valve</b>                      | Rapid Action Hydroseal   |
| <b>Turning Type</b>                           | Comes standard with Rapid Action (1/4 Turn)  |
| <b>Outlet Type</b>                            | Swivel Outlet, Optionally Fixed on Installation  |
| <b>Outlet Styling</b>                         | Sink Gooseneck Outlet  |
| <b>Outlet Reach (mm to Aerator or Rose)</b>   | 215  |
| <b>Water Efficiency Star (WELS) Rating</b>    | N/A  |
| <b>Flow Rate (Litres Per Minute)</b>          | No   |
| <b>Suitable for Gravity Feed</b>              | Yes  |
| <b>Suitable for Hot Water Units</b>           | Yes  |
| <b>Maximum operating pressure (KPA)</b>       | Suitable for High/Mains Pressure / 500 KPA (Australian Standards AS/NZS 3500 and the Plumbing Code of Australia) |
| <b>Maximum Working Temperature (Degree C)</b> | 65   |
| <b>Relevant Standards</b>                     | AS/NZS 3718:2005, AS/NZS 4020:2005   |
| <b>Quantity Unit of Measure</b>               | Set  |
| <b>Warranty</b>                               | 5 Years  |
| <b>WELS Licence</b>                           | WELS Rating Not Required   |
| <b>WELS Registration</b>                      | Not Applicable   |