

Product Function	Flick Mixer
Style Association	DB Series
Material	DR Brass
Handle Type	Lever Handle
Cartridge / Valve	Ceramic Cartridge
Outlet Type	Swivel Only
Outlet Styling	Duck Bill Outlet
Outlet Reach (mm to Aerator or Rose)	105mm (125mm Centre to Centre)
Overall Height	140mm
Outlet Height	55mm
Standard Base Cover Size	50mm Outside Diameter
Connections	Standard Hot and Cold Hoses
Installation Requirement	Minimum 33mm diameter bench hole required. 2 x Flexible hoses supplied, for connecting to 1/2" BSP male water source.
Water Efficiency Star (WELS) Rating	4 Stars
Flow Rate (Litres Per Minute)	7.5 Litres Per Minute
Suitable for Gravity Feed	No
Suitable for Hot Water Units	Yes
Maximum operating pressure (KPA)	Suitable for High/Mains Pressure / 500 KPA (Australian Standards AS/NZS 3500 and the Plumbing Code of Australia)
Maximum Working Temperature (Degree C)	65
Relevant Standards	AS/NZS 3718:2005, AS/NZS 4020:2005
Quantity Unit of Measure	Each
Warranty	5 Years
WELS Licence	WELS Licence 0091
WELS Registration	T08569