

<b>Product Function</b>	Basin Set
<b>Style Association</b>	Roulette
<b>Material</b>	DR Brass
<b>Handle Type</b>	Cross Handle
<b>Spindle Type</b>	Splined Spindle
<b>Cartridge / Valve</b>	Jumper Valve
<b>Turning Type</b>	Full Turn Standard Action, is upgradable to Rapid Action (1/4 Turn) with Hydroseal Valve
<b>Outlet Type</b>	Swivel Outlet, Optionally Fixed on Installation
<b>Outlet Styling</b>	Basin Upswept Outlet
<b>Outlet Reach (mm to Aerator or Rose)</b>	150
<b>Water Efficiency Star (WELS) Rating</b>	4 Stars
<b>Flow Rate (Litres Per Minute)</b>	7.5 Litres Per Minute
<b>Suitable for Gravity Feed</b>	Yes
<b>Suitable for Hot Water Units</b>	Yes
<b>Maximum operating pressure (KPA)</b>	Suitable for High/Mains Pressure / 500 KPA (Australian Standards AS/NZS 3500 and the Plumbing Code of Australia)
<b>Maximum Working Temperature (Degree C)</b>	65
<b>Relevant Standards</b>	AS/NZS 3718:2005, AS/NZS 4020:2005
<b>Quantity Unit of Measure</b>	Set
<b>Warranty</b>	5 Years
<b>WELS Licence</b>	WELS Licence 0091
<b>WELS Registration</b>	T29370